

**Product Name**

QuickGuard™ Asset Identification Tags

**Associated Specification Section**

Section 01592 - Property Identification Tags

**Manufacturer's Name**

Seton Identification Products

Page 1

2003-02-26

**PRODUCT DESCRIPTION**

---

**PRODUCT FEATURES**

- BASIC USES / RELATED USES
  - Identification tags to track and identify assets.
  - Long term Indoor and Outdoor use.
- PRODUCT ATTRIBUTES AND CHARACTERISTICS
  - Material: Anodized aluminum with permanent adhesive, in six (6) colors, with reverse or positive printing via roller.
  - Lettering:
    - Preprinted "Property of ....." if required.
    - Numbering - sequentially or none.
    - Four (4) standard font type styles.
  - Accessories:
    - A permanent marking pen.
  - Performance:
    - Tamper resistant - cannot be rubbed or scratched off.
    - Stands up to solvents and abrasion.
    - Withstand temperatures from -40° C - 121°C (-40° F to 250° F).
    - Temperature Range:
      - \* Stock tag: -40° to 121° C (-40° to 250° F).
      - \* Custom tag: -40° to 149° C (-40° to 300° F).
  - Simple to apply to clean, dry surface with minimum temperature of 4° C (40° F).
- SELECTION CRITERIA
  - Black and Dark Blue colored tags are best for long term outdoor use.
- PACKAGING, HANDLING, PROTECTION, AND DELIVERY INSTRUCTIONS
  - Next day shipping for minimum orders.
  - Minimum application temperature 4° C (40° F).
  - Ten (10) labels per strip with one hundred (100) per package.
- AVAILABILITY
  - Direct from Seton, by telephone, fax, mail, or online methods.
- COST
  - Depends on quantity, customization, and complexity of text and use of artwork for logos.

**PRODUCT PROPERTIES**

- MATERIALS AND PROPERTIES

**Product Name**

QuickGuard™ Asset Identification Tags

**Associated Specification Section**

Section 01592 - Property Identification Tags

**Manufacturer's Name**

Seton Identification Products

Page 2

2003-02-26

**PRODUCT DESCRIPTION**

- Anodized aluminum material 0.075 mm (0.003") thick, matte finish, with permanent adhesive backing.
- Adhesive:
  - 3M #467 permanent type, is for most smooth non-plastic surfaces,
  - 3M #468 permanent type, is for rough or textured non-plastic surfaces, and
  - 3M #9471 is for smooth plastic surfaces.
- Lettering:
  - Permanently debossed numbering in positive or reverse printing.
  - Text: 3 mm (1/8") high with 6 digits for numbering.
  - Custom wording and logos - your company logo, camera artwork, numbering or individual names.
- **ACCESSORIES**
  - Permanent marking pen for writing on vinyl, polyester, plastic, aluminum, metal, brass, fiber, and glass on dry, cold, or wet surfaces. Colors: Black, Green, Red, and Blue.
  - Roller: 25 mm (1") name plate roller to ensure uniform adhesion.
- **SIZES**
  - Sizes of standard tags:
    - 38 mm wide x 13 mm high (1-1/2" wide x 1/2" high),
    - 38 mm wide x 19 mm high (1-1/2" wide x 3/4" high),
    - 51 mm wide x 13 mm high (2" wide x 1/2" high),
    - 51 mm wide x 19 mm high (2" wide x 3/4" high).
  - Custom sizes available:
    - 25 mm x 25 mm (1" wide x 1" high),
    - 64 mm x 19 mm (2-1/2" wide x 3/4" high),
    - 51 mm x 25 mm (2" wide x 1" high),
    - 76 mm x 25 mm (3" wide x 1" high),
    - 64 mm x 25 mm (2-1/2" wide x 1" high),
    - 70 mm x 25 mm (2-3/4" wide x 1" high),
    - 76 mm x 38 mm (3" wide x 1-1/2" high),
    - 51 mm x 38 mm (2" wide x 1-1/2" high),
    - 102 mm x 38 mm (4" wide x 1-1/2" high).
  - For logo with additional sizes, colors, or type styles, phone 800-571-2596 for more information. Custom artwork is available.
- **TEXT AND FINISH**
  - Finish:
    - Positive printed plate - wording is aluminum and the background is colored.
    - Reverse printed plate - wording is colored and the background is aluminum.
  - Four (4) font types:
    - Helvetica, Helvetica Bold, Helvetica Italic Bold, Helvetica Italic.
  - Six (6) colors: Dark Blue, Dark Red, Dark Green, Black, Light Blue, and Flame Red.

**Product Name**

QuickGuard™ Asset Identification Tags

**Associated Specification Section**

Section 01592 - Property Identification Tags

**Manufacturer's Name**

Seton Identification Products

Page 3

2003-02-26

**PRODUCT DESCRIPTION****PRODUCT PLACEMENT**

- **PREPARATION**
  - Select the best location for the tags position - hidden is best.
  - Ensure area is flat and smooth.
  - Ensure surfaces are clean and free of contaminants.
  - Clean with a cleaning solvent or alcohol if necessary and let dry.
  
- **APPLICATION**
  - Apply firm pressure with roller to ensure total contact of the adhesive with the asset surface.
  - Apply tags at 4° C (40° F) minimum application temperature.
  - Do not touch the adhesive on the back of the tag.
  - Bond strength will increase in strength after 48 hours the application will be two times as strong after the first hour. Bond strength will increase up to one year.
  
- **MAINTENANCE INSTRUCTIONS AND PROCEDURES**
  - Clean with clear water and mild soap.

**Corporate Identification**

Seton Identification Products  
Dept. AT-21  
20 Thompson Road  
P.O. Box 819  
Branford, CT 06405-0819  
Tel: 800-243-6624  
Fax: 800-345-7819  
Website: [www.seton.com](http://www.seton.com)

**Technical Services Available**

Architects: Product binder, specifications on disk and available on Seton web site..  
Contractors: Submittal binder.

**Classification and Filing**

MasterFormat:  
Section 01592 - Property Identification Tags

UniFormat:  
N/A

**END**