

## PRODUCT DATA SHEET

### Poly-Code™ Clear Pipe Markers

- Clear pipe markers let pipe color show through
- Coated with a permanent acrylic adhesive to prolong the life of the marker suitable for indoor and outdoor use
- Resists tearing, heat and abrasion

**Description:**

Poly-Code™ Clear Pipe Markers are printed on durable polyester that have a clear background with either white or black lettering to identify your pipe contents. They are coated with a permanent acrylic adhesive and designed for use on pipes from 3/4" to over 10" both indoors and outdoors.

**Use:**

Poly-Code™ Clear Pipe Markers are intended for colored pipes to clearly identify pipe contents in commercial and industrial areas.



**Adhesive Type:**

Self-adhesive

**Compliance:**

Poly-Code™ Clear Pipe Markers meet ASME/ANSI A13.1 standard for letter height

**Standard Legend Colors:**

Black and White

**Standard Background Colors:**

Clear

**Thickness (PSTC-33):**

2 mil

**Standard Sizes/Dimensions:**

Marker Size:	8SM	8LG	12	24	32
Size of Pipe Diameter Markers Used on:	3/4" Thru 1-3/8"	1-1/2" Thru 2-3/8"	2-1/2" Thru 7-7/8"	8" Thru 10"	Diameters over 10"
Marker Size:	2-1/4" x 8"	2-1/4" x 8"	2-1/4" x 12"	4" x 24"	4-1/2" x 32"
Poly-Code™ Markers have the length of clear and field & size of letters to match ASI specs:	8" Long Clear Field 1/2" Letters	8" Long Clear Field 3/4" Letters	12" Long Clear Field 1-1/4" Letters	24" Long Clear Field 2-1/2" Letters	32" Long Clear Field 3-1/2" Letters
Max. No. of Letters:	23	15	26	24	23

**Minimum Application Temperature:**

32°F to 100°F (0°C to 38°C)

Date: \_\_\_ / \_\_\_ / \_\_\_ Job: \_\_\_\_\_

Contractor \_\_\_\_\_



Signs, Labels & Solutions for a Safer Workplace

877.367.7732 seton.com

Fax 800.345.7819

Email [submittals@seton.com](mailto:submittals@seton.com)

P.O. Box 458, Buffalo, NY 14240-0458

## PRODUCT DATA SHEET

### Poly-Code™ Clear Pipe Markers (continued)

**Service Temperature:** -20°F to 257°F (-29°C to 125°C)

**Average Outdoor Durability:** 3 to 5 years (Average expected outdoor life of product will depend on user definition of failure, climatic conditions, mounting techniques, and material color).

Date: \_\_\_ / \_\_\_ / \_\_\_ Job: \_\_\_\_\_

Contractor \_\_\_\_\_