

SELECTION GUIDE

Choosing Anti-slip Floor Decals

Material Selection

Choose from three materials to fit your facility.

Materials:

MATERIAL	BENEFITS	SPECIFICATIONS	THICKNESS	ADHESIVE
Light-duty	<ul style="list-style-type: none">• Flexible• Last for years in heavy foot traffic• Easy to apply	<ul style="list-style-type: none">• Self-adhesive vinyl material• Doesn't break down with clear, anti-slip overlay• Extra-strength adhesive	6-mil.	<ul style="list-style-type: none">• Permanent acrylic adhesive that won't shrink decal• Medium tack• Resists chemicals• Developed for clarity in application
Heavy-duty	<ul style="list-style-type: none">• Extremely durable• Chemical and solvent resistant• Does well in vehicle and forklift traffic environments• Easy to apply	<ul style="list-style-type: none">• Self-adhesive vinyl material• Non-slip Lexan coating• Extra-strength adhesive• Graphics subsurface printed to withstand abuse• No chipping or cracking	6-mil.	<ul style="list-style-type: none">• Permanent acrylic adhesive that won't shrink decal• High tack• Resists chemicals• Adheres well to cold floors
Cold-adhesion	<ul style="list-style-type: none">• Stop slips and falls on cold floors• Works best in freezers, unheated warehouses, and outdoor storage areas• Easy to apply	<ul style="list-style-type: none">• Self-adhesive vinyl material• Non-slip Lexan coating• Extra-strength adhesive• Applies to surfaces with temperatures as low as -40°F• Graphics subsurface printed to withstand abuse• No chipping or cracking	6-mil.	<ul style="list-style-type: none">• Permanent acrylic adhesive that won't shrink decal• High tack• Resists chemicals• Service temperature range is -40°F to 176°F (-40°C to 80°C)

SELECTION GUIDE

Size Selection

There are three sizes of anti-slip floor decals. Each is made to suit a different environment.

Sizes:

SIZE	BENEFITS
7-1/2" diameter	Ideal for slip-protection on narrow paths or steps.
17" diameter	Perfect for creating a pathway that directs traffic while decreasing slips.
24" diameter	Well-suited to curb accidents on slippery floors and message forklift drivers and staff.

Installation

Anti-slip floor decals are easy to install. A plastic backing is removed to expose a tacky adhesive. (See the guide above to know what decal is for your floor.)

1. Clean surface that decal will be applied to.
2. Make sure the surface is dried after cleaning. (No liquid should be present when applying adhesive.)
3. Peel layer off the back of your decal (the non-textured side).
4. Press tacky-side of decal to floor.