



Pipe Marker Selection Guide



Material	Vinyl	Over-Laminated Vinyl	Vinyl	Over-Laminated Polyester																																								
Material Thickness	.005 IN (0.125 MM)	.005 IN	.020 IN (0.51 MM) / .030 IN (0.76 MM)	.007 IN (0.178 MM)																																								
ANSI/ASME A13.1 Compliant	* <small>*When used with Arrows-On-a-Roll™ Tape</small>																																											
Mounting	Pressure Sensitive Adhesive	(0.125 MM) Pressure Sensitive Adhesive	Coiled Nylon Ties (included)	Coiled with Adhesive Strip Nylon Ties (included)																																								
Application Method	Self-Adhesive Back	Self-Adhesive Back	8XS-12MD Snap-Around (fits O.D. 3/8 IN to 5 7/8 IN) 12LG - 32 Strap-Around (fits O.D. 6 IN -10 IN+)	8SM-12LG Adhesive Strip (fits O.D. up to 8 IN) 24-32 Strap-Around (fits O.D. 8 IN+)																																								
Standard / Custom Background & Text Colors	<table border="1"> <tr><td>W/G</td><td>W/G</td><td>B/O</td><td>W/R</td><td>W/B</td></tr> <tr><td>W/B</td><td>B/Y</td><td>W/B</td><td>B/W</td><td>W/P</td></tr> </table>	W/G	W/G	B/O	W/R	W/B	W/B	B/Y	W/B	B/W	W/P	<table border="1"> <tr><td>W/G</td><td>W/G</td><td>B/O</td><td>W/R</td><td>W/B</td></tr> <tr><td>W/B</td><td>B/Y</td><td>W/B</td><td>B/W</td><td></td></tr> </table>	W/G	W/G	B/O	W/R	W/B	W/B	B/Y	W/B	B/W		<table border="1"> <tr><td>W/G</td><td>W/G</td><td>B/O</td><td>W/R</td><td>W/B</td></tr> <tr><td>W/B</td><td>B/Y</td><td>W/B</td><td>B/W</td><td></td></tr> </table>	W/G	W/G	B/O	W/R	W/B	W/B	B/Y	W/B	B/W		<table border="1"> <tr><td>W/G</td><td>W/G</td><td>B/O</td><td>W/R</td><td>W/B</td></tr> <tr><td>W/B</td><td>B/Y</td><td>W/B</td><td>B/W</td><td></td></tr> </table>	W/G	W/G	B/O	W/R	W/B	W/B	B/Y	W/B	B/W	
W/G	W/G	B/O	W/R	W/B																																								
W/B	B/Y	W/B	B/W	W/P																																								
W/G	W/G	B/O	W/R	W/B																																								
W/B	B/Y	W/B	B/W																																									
W/G	W/G	B/O	W/R	W/B																																								
W/B	B/Y	W/B	B/W																																									
W/G	W/G	B/O	W/R	W/B																																								
W/B	B/Y	W/B	B/W																																									
Fade-Resistant UV Ink																																												
Directional Flow Arrows	* <small>*When used with Arrows-On-a-Roll™ Tape</small>																																											
Service Temperatures	-40°F to 180°F (-40°C to 82°C)	-40°F to 248°F (-40°C to 120°C)	-40°F to 180°F (-40°C to 82°C)	-40°F to 248°F (-40°C to 120°C)																																								
Marker Visibility	Front Facing	Front Facing	360°	360°																																								
Pipe Surface	Clean / Dry / Insulated	Clean / Dry / Insulated	Clean / Dry / Dirty Rough / Insulated / Wet Greasy / Oily	Clean / Dry / Dirty Rough / Insulated / Wet Greasy / Oily																																								
Reusability																																												
Environmental Application	Indoor/ Outdoor (Up to 5 years Outdoor)	Indoor/ Outdoor (Up to 5 years Outdoor)	Indoor/ Outdoor (Up to 8 years Outdoor)	Indoor/ Outdoor (Up to 8 years weather & humidity resistance)																																								
Chemical Resistance	Rub Resistance: Acids / Alkalis Ammonia / Oil	Rub Resistance: Acids / Alkalis / Alcohols Fuels / Solvents / Oils Ammonia	Dip & Rub Resistance: Acids / Alkalis / Alcohols Fuels / Solvents / Oils Ammonia	7-Day Immersion Resistance: Acids / Alkalis / Alcohols Fuels / Solvents / Oils Ammonia																																								
Recommended Industries	Indoor Use / Commercial Facilities	Indoor Use / Commercial Facilities	Factory / Warehouse / Construction	Chemical Process Plants / Oil & Gas Facilities																																								
Customizable																																												

Don't see what you're looking for? Not sure which Pipe Marker is right for your project? Contact our expert team. CALL 1.877.367.7732 VISIT SETON.COM